

Specifications

ACP 106 D Control Panel

ACP Control Interface

ACP control ports	(2) 3.5 mm captive screw connectors, 4 pole
ACP pin configuration	+V = +12 VDC; +S = + signal; -S = - signal; G = ground
Recommended cable type.....	Extron STP20-2/1000 or STP20-2P/1000 cable

Software Configuration

Software	Extron DSP Configurator
----------------	-------------------------

General

Power	Power is supplied by an ACP enabled processor or optional power supply
ACP power consumption.....	1.5 watts, 12 VDC (Device only)
Temperature/humidity	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Cooling	Convection, no vents
Mounting	
Rack mount.....	No
Furniture or wall mount.....	Yes, in a standard US 1-gang electrical junction box or mud ring
Enclosure type	Plastic faceplate, metal mounting plate
Enclosure dimensions	
Coverplate.....	4.5" H x 2.8" W x 0.3" D (11.4 cm x 7.1 cm x 0.7 cm)
Faceplate	4.2" H x 1.8" W x 0.8" D (10.5 cm x 4.5 cm x 2 cm) (Fits the opening in a 1-gang decorator-style wallplate)
Device.....	2.7" H x 1.7" W x 0.8" D (6.9 cm x 4.2 cm x 2 cm) (Depth excludes faceplate and buttons)
Device and captive screw	2.7" H x 1.7" W x 1.25" D (6.9 cm x 4.2 cm x 3.2 cm)
Product weight	0.2 lbs (0.1 kg)
Vibration	ISTA 1A in carton (International Safe Transit Association)
Regulatory compliance	
Safety.....	CE, c-UL, UL
EMI/EMC.....	CE, C-tick, FCC Class A, ICES, VCCI Class A
Environmental.....	Complies with the appropriate requirements of RoHS, WEEE
Accessibility.....	Complies with the appropriate requirements of Section 508 of the Rehabilitation Act (29 U.S.C. 794d)
Warranty	3 years parts and labor

NOTE: All nominal levels are at $\pm 10\%$

NOTE: Specifications are subject to change without notice

NOTE: Shipping weights and dimensions are available at www.extron.com.

040717-D2