

# Specifications — RCP 2000 Remote Control Panel

---

## Control/remote — control panel

Serial control port .....	RS-232, 9-pin female D connector
Baud rate and protocol .....	9600, 8-bit, 1 stop bit, no parity
Serial control pin configurations	2 = TX, 3 = RX, 5 = GND
Ethernet control port .....	1 RJ-45 female connector
Ethernet data rate .....	10/100Base-T, half/full duplex with autodetect
Ethernet protocol .....	ICMP (ping), TCP/IP, Telnet
Program control .....	Extron's control program for Windows® Extron's Simple Instruction Set (SIS™) Microsoft Explorer, Netscape Navigator, Telnet

## General

Power .....	100VAC to 240VAC, 50/60 Hz, 60 watts, internal, autoswitchable
Temperature/humidity .....	Storage -40° to +158°F (-40° to +70°C) / 10% to 90%, noncondensing Operating +32° to +122°F (0° to +50°C) / 10% to 90%, noncondensing
Rack mount .....	No
Enclosure type .....	Metal
Enclosure dimensions .....	5.5" H x 17.0" W x 12.0" D 14.0 cm H x 43.2 cm W x 30.5 cm D (Depth excludes connectors and knobs.)
Product weight .....	15 lbs (6.8 kg)
Shipping weight .....	22 lbs (10 kg)
Vibration .....	ISTA 1A in carton (International Safe Transit Association)
Listings .....	UL, CUL
Compliances .....	CE, FCC Class A, VCCI, AS/NZS, ICES
Warranty .....	3 years parts and labor

**NOTE** *Specifications are subject to change without notice.*

(7.50+051004-D4) -112012