
Audio output

| | |
|-------------------------------|--|
| Number/signal type | 1 stereo (2 channel), balanced/unbalanced |
| Connectors | 3.5 mm stereo captive screw connector, 5 pole, for left and right output |
| Impedance | 50 ohms unbalanced, 100 ohms balanced |
| Gain error | ±0.1dB channel to channel |
| Maximum level (600 ohm) | +14dBu, balanced at stated %THD+N |

NOTE 0dBu = 0.775 volts (RMS).

General

| | |
|----------------------------|--|
| Power | 100VAC to 240VAC, 50/60 Hz, 15 watts, internal, auto-switchable |
| MBC power jack | 9.0VDC, 150 mA |
| Temperature/humidity | Storage -40° to +158°F (-40° to +70°C) / 10% to 90%, non-condensing Operating +32° to +122°F (0° to +50°C) / 10% to 90%, non-condensing |
| Rack mount | Yes, with included kit #70-077-03 |
| Furniture mount | Yes, with optional kit #70-077-01 (under desk) or included kit #70-077-03 (through desk/rack mount) |
| Enclosure type | Metal |
| Enclosure dimensions | 1.75" H x 17.5" W x 6" D 4.5 cm H x 44.5 cm W x 15.2 cm D (Depth excludes connectors and knobs. Width excludes rack ears.) |
| Shipping weight | 7 lbs (3.2 kg) |
| Vibration | ISTA/NSTA 1A in carton (International Safe Transit Association) |
| Approvals | UL, CE, FCC Class A |
| MTBF | 30,000 hours |
| Warranty | 2 years parts and labor |

NOTE Specifications are subject to change without notice.

(7.0-030801-D1)