



Specifications

TeamWork® 601 Kit

TRUE 4K

Switcher

Max. 4K Capabilities		
Resolution and Refresh Rate	Chroma Sampling	Max. Bit Depth per Color
4096x2160 at 30 Hz	4:4:4	8 bit
3840x2160 at 30 Hz		

- Maximum data rate 10.2 Gbps (3.4 Gbps/color)
- Maximum pixel clock..... 297 MHz
- Resolution
 - HDMI..... Up to 1920x1200 @ 60 Hz, or 1080p @ 60 Hz and 2K, 12-bit color, 4K (4096x2160) @ 30 Hz or 4K UHD (3840 x 2160) @ 30Hz, 8-bit color
 - VGA 640x480 @ 60Hz to 2048x1080 @ 60 Hz
- Serial control port..... (1) RS-232, 3.5 mm captive screw connector, 3 pole
- Contact closure (6) 3.5 mm captive screw connector, 3 pole (shared with Tally output)
- Tally output (6) 3.5 mm captive screw connector, 3 pole (shared with Contact closure)
- Power supply External,
Input: 100-240 VAC, 50-60 Hz
Output: 12 VDC, 0.5 A, 6 watts
- Power consumption
 - Device 3.9 watts, 12 VDC
 - Device and power supply 5.3 watts, 12 VDC
- Enclosure dimensions 1.75" H x 8.75" W x 6.00" D (1U high, half rack wide)
(44 mm H x 222 mm W x 152 mm D)
(Depth excludes connectors)

System Controller

- Connectors..... 1 female USA/Edison power connector
- Voltage..... 120 VAC, 50-60 Hz
- Maximum AC load 12A, 1440 watts at 120 VAC
- Serial control port..... (1) RS-232 only, 3.5 mm captive screw connector, 4 pole
- Serial control pin configuration 1 = Tx, 2 = Rx, 3 = GND
- Power supply Internal:
100-240 VAC, 50-60 Hz, 5 watts
- Enclosure dimensions 1.75" H x 4.30" W x 6.00" D (1U high, quarter rack wide)
(44 mm H x 109 mm W x 152 mm D)
(Depth excludes connectors)

Specification • TeamWork 601 Kit (Continued)

Cable Cubby®

Min./max. table thickness	0.50" to 2.50" (13 mm to 64 mm)
Top plate (outer rim)	10.57" W x 7.42" D (269 mm W x 189 mm D)
Enclosure depth.....	4.46" H (113 mm H)
Surface cutout (inside rim).....	10.00" W x 6.75" D (254 mm W x 171 mm D)

HDMI SM Show Me® Cable

Standards	High speed HDMI® cable
Resolution range.....	HDMI cable: Up to 4K @ 60 Hz (4096x2160) or UHD @ 60 Hz (3840x2160) 8 bit color depth, max. 18.0 Gbps data rate
Contacts	Gold Plated
Material.....	Conductors: tinned copper, 30 AWG Drain wire: tinned copper, 32 AWG Shielding: fluorocopolymer tape binder, tinned copper braid
Overall length	6' (1.8 m) measured neck-to-neck

VGA SMC Show Me Cable

Connector type	1 male 15-pin HD to 1 male 15-pin HD
Material.....	Conductors: tinned copper, 30 AWG Drain wire: tinned copper, 30 AWG
Overall length	6' (1.8 m) measured neck-to-neck

General

Regulatory compliance	
Accessibility.....	Complies with the appropriate requirements of Section 508 of the Rehabilitation Act (29 U.S.C. 794d).
Warranty	3 years parts and labor.

NOTES:

- For the complete specifications for each component of the kit, see www.extron.com.
- Specifications are subject to change without notice.
- Shipping dimensions and weights are available at www.extron.com.