

Specifications — WP Series Wall Plates

General

Temperature/humidity	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing
Rack mount	No, but furniture/wall mountable.
Enclosure type	Metal
Dimensions	
1-gang models	
Faceplate	4.5" H x 2.8" W x 0.1" D (11.4 cm H x 7.1 cm W x 0.3 cm D) (1 gang)
Boards	2.6" H x 1.75" W x 1.1" D (6.6 cm H x 4.4 cm W x 2.8 cm D) (Depth includes rear connectors. Allow at least 2.5" (6.4 cm) depth within the wall box or furniture to accommodate the circuit board, connectors, and cables.)
AUS models	
Faceplate	3.0" H x 4.7" W x 0.1" D (7.6 cm H x 11.8 cm W x 0.3 cm D)
Boards	1.75" H x 2.6" W x 1.1" D (4.4 cm H x 6.6 cm W x 2.8 cm D) (Depth includes rear connectors. Allow at least 2.5" (6.4 cm) depth within the wall box or furniture to accommodate the circuit board, connectors, and cables.)
Product weight	0.2 lbs (0.1 kg)
Shipping weight	1 lbs (1 kg)
Vibration	ISTA 1A in carton (International Safe Transit Association)
Listings	UL, CUL
Compliances	FCC Class A, VCCI, AS/NZS, ICES as components of the MLC 206
Warranty	3 years parts and labor

NOTE *Specifications are subject to change without notice.*

(7.51-021105-D4-112012)