Extron

Specifications

PI 130

General

Connectors	1 RJ-45 female connector for pass-through input 1 RJ-45 female connector for pass-through and power output
Ethernet standards	10/100/1000Base-T
Power supply	Internal Input: 100-240 VAC, 50-60 Hz
Power input	
No load	100 VAC to 240 VAC, 50-60 Hz, 0.8 watts
Full power	100 VAC to 240 VAC, 50-60 Hz, 34.2 watts, 0.6 A maximum
Power output	56 VDC, 0.5 A, 30 watts Compatible with 802.3at PoE+ devices
Efficiency	
At full load, 230 VAC	89.30%
At full load, 100 VAC	87.70%
Power consumption	
No load	100 VAC to 240 VAC, 50-60 Hz, 0.86 watts
Full load	100 VAC to 240 VAC, 50-60 Hz, 30 watts
Temperature/humidity	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Cooling	Convection, no vents
Mounting	
Rack mount	Yes, with optional 1U rack shelf with the included ZipClip 200 mounting clip or by securing to rack rails with tie wraps
Furniture mount	Yes, with the included ZipClip 200 mounting clip
Pole mount	Yes, using tie wraps
Enclosure type	High impact, high temperature plastic
Enclosure dimensions	1.7" H x 4.3" W x 4.5" D (1U high, quarter rack wide) (4.2 cm H x 11.0 cm W x 11.4 cm D)
Product weight	0.6 lb (0.3 kg)
Regulatory compliance	
Safety, EMI/EMC	BIS, CE, C-tick, c-UL, UL, CISPR 32, CISPR 35, FCC Class B, NEC Class 2
Environmental	Complies with the appropriate requirements of RoHS, WEEE.
Product warranty	7 years parts and labor

NOTE: Specifications are subject to change without notice.

NOTE: Shipping dimensions and weights are available at **www.extron.com**.

6513-D3